

- Material:UL approved nylon PA66,Nitrilebutadienerubber(NBR).
- Thead specification:Metric,PG,G,NPT.
- Working temperature:-40℃ to 100℃ instatic state,instantaneous heat resistance up to 120℃,-20℃ to 80℃ in dynamic stae instantaneous heat resistan up to 100℃.
- Characteristics:special design of clamping die and rubber part,large range in clamping cable,ultra-strong stretching resistance,waterproof,dustpoof,and high ability to resist,salt,acid,alkali,alcohol,grease and general slovent.
- Color: Black,grey as special colors(white,red,blue,daud grey)that can be designed at request.

产品型号 Model	 螺纹尺寸 mm	 螺纹长度 mm	 适用电缆 mm	 扳手尺寸 mm	 包装数量 PCS
PG7	12.5	9	3.5~6.5	18/16	100/5000
PG7	12.5	9		18/16	100/5000
PG9	15.2	9	4~8	22/19	100/3500
PG9	15.2	9		22/19	100/3500
PG11	18.6	9	5~11	24/22	100/2500
PG11	18.6	9		24/22	100/2500
PG13.5	20.4	9	6~12	27/24	100/2000
PG13.5	20.4	9		27/24	100/2000
PG16	22.5	10	10~14	30/27	100/1500
PG16	22.5	10		30/27	100/1500
PG19	24	10	12~15	30/28	100/1200
PG19	24	10		30/28	100/1200
PG21	28.3	12	13~18	36/33	100/1000
PG21	28.3	12		36/33	100/1000
PG25	30	12	16~21	37/35	50/800
PG25	30	12		37/35	50/800
PG29	37	12	18~25	45/42	50/450
PG29	37	12		45/42	50/450
PG36	47	17	22~32	58/42	20/240
PG36	47	17		58/52	20/240
PG42	54	18	32~39	65/60	20/200
PG42	54	18		65/60	20/200
PG48	59.3	19	37~44	70/69	15/150
PG48	59.3	19		70/69	15/150
PG63	71	27	42~51	83/75	10/80
PG63	71	27		83/75	10/80

