

PG Brass Specification

CE RoHs SGS

- Material: The main body made of nickel-plated brass, clamp pieces make of UL approved nylon PA, O-sealing make of nitrilebutadienerubber(NBR), weathering rubber(EPDM).
- Thread specification: Metric, PG, G, NPT.
- Working temperature: -40℃ to 100℃ instatic state, instantaneous heat resistance up to 120℃, -20℃ to 80℃ in dynamic stae instantaneous heat resistan up to 100℃.
- Portection Class: IP68(using O-sealing).

PG TYPE

产品型号 Model	 AG 螺纹尺寸 mm	 螺纹长度 mm	 适用电缆 mm	 扳手尺寸 mm	 包装数量 PCS
TPG7	12.5	7	3~6.5	14	100/1600
TPG7	12.5	7		14	100/1600
TPG9	15.2	7	4~8	17	100/800
TPG9	15.2	7		17	100/800
TPG11	18.6	7	5~10	20	100/400
TPG11	18.6	7		20	100/400
TPG13.5	20.4	8	6~12	22	100/400
TPG13.5	20.4	8		22	100/400
TPG16	22.5	8	10~14	24	100/450
TPG16	22.5	8		24	100/450
TPG21	28.3	8	13~18	30	400
TPG21	28.3	8		30	400
TPG29	37.0	11	18~25	40	120
TPG29	37.0	11		40	120
TPG36	47.0	13	22~32	50	80
TPG36	47.0	13		50	80
TPG42	54.0	13	32~38	60	48
TPG42	54.0	13		60	48
TPG48	59.3	14	37~44	65	27
TPG48	59.3	14		65	27
TPG63	72.0	15	42~52	78	15

