


TD Lighting Solutions

X-MS50172NCxx-NVSW319B-12

Square Series

www.tlsteknoloji.com

PRODUCT PHOTO



SPECIFICATIONS


- Default driving method is constant current input
- CCT Range from 2700K up to 6500K
- This module can be used as 12 series.
- Luminous flux range from 1875 lm to 7094 lm
- Efficacy of the module up to 180 lm/W
- CRI 80 is standard. CRI 70 and CRI 90 is available.
- Outstanding system color tolerance MacAdam 3 over the full operating area
- Simple installation (e.g. screw)
- Long life-time > 60,000 hours
- 5 years guarantee at specified conditions



For your orders please call us:


+90 444 27 33

APPLICATIONS



High Bay Lighting Very High Bay
Lighting


PHOTOMETRY



TECHNICAL DATA

Beam Angle	120°
Ambient temperature range	-25° ~ +55°C
Tc max	100°C
Max. DC forward current	1400mA
Typical voltage of LED Module at max current	37 V
Insulation test voltage	2kV
ESD classification	Class 1
Risk group (EN 62471:2008)	2
Type of protection	IP00

ORDERING INFORMATION



DRIVING CURRENT VS LUMEN OUTPUT SPECIFICATION

Common Characteristic [Tj : 85°C] ;			
Module Code	X-MS50172NCxx-NVSW319B-12		
PCB Material	ALU	Electrical Connection	
Operating Temperature (°C)	-40 ~ +100	Parallel	1
Storage Temperature (°C)	-40 ~ +55	Series	12
Thermal Conductivity (W/m-K)	1>	LED Quantity	12
LED NVSW319B_R8000			
Correlated Color Temperature (CCT)	4000K		
Color Rendering Index (CRI)	80+		
Module Operating Voltage (V)	33	34	35,88
Module Operating Current (mA)	350	700	1400
Branch Operating Current (mA)	350	700	1400
Module Power (W)	11,42	23,86	50,23
Module Light Output (lm)	1.885	3.602	6631
Module Efficiency (lm/W)	165	151	132
LED NVSW219F-V1_R8000			
Correlated Color Temperature (CCT)	4000K		
Color Rendering Index (CRI)	80+		
Module Operating Voltage (V)	33	35	36,72
Module Operating Current (mA)	350	700	1400
Branch Operating Current (mA)	350	700	1400
Module Power (W)	11,72	24,36	51,41
Module Light Output (lm)	1.875	3.557	6477
Module Efficiency (lm/W)	160	146	126
LED NVSW219F_R70			
Correlated Color Temperature (CCT)	4000K		
Color Rendering Index (CRI)	70+		
Module Operating Voltage (V)	33	35	36,72
Module Operating Current (mA)	350	700	1400
Branch Operating Current (mA)	350	700	1400
Module Power (W)	11,72	24,36	51,41
Module Light Output (lm)	2.109	3.946	7094
Module Efficiency (lm/W)	180	162	138


The table below shows how to Module Light Output changes depending on CCT (°K)

Lumen Output Multiplier					
LED	2700°K (CRI 80)	3000°K (CRI 80)	4000°K (CRI 80)	5000°K (CRI 80)	6500°K (CRI 80)
NVSW319B_R8000	0,92	0,94	1,00	1,01	0,98
NVSW219F-V1_R8000	0,88	0,92	0,96	0,97	0,94


Lumen Output Multiplier					
LED	2700°K (CRI 70)	3000°K (CRI 70)	4000°K (CRI 70)	5000°K (CRI 70)	6500°K (CRI 70)
NVSW219F_R70	0,93	0,95	1,00	1,01	X

Relative luminous intensity versus CCT (°K)

X-MS50172NCxx-NVSW319B-12 MECHANICAL DRAWINGS




SERBEST ÖLÇÜ TOLERANSLARI -DIN 2768-1 / General Tolerances for linear and angular dimensions (DIN ISO 2768-1)

0.5 up to 3mm		over 3 up to 6mm		over 6 up to 30mm		over 30 up to 120mm		over 120 up to 400mm		over 400 up to 1000mm			
± 0.1		± 0.1		± 0.2		± 0.3		± 0.5		± 0.8			
Stock code No				MALZEME (MATERIAL) XXX		AGIRLIK (WEIGHT) XXX							
Revision		00											
Date		10.12.2019		TLS-001-10S50172NC35-12						OLÇEK / SCALE		A4	
Sheet													
Drawn By		Kaan ALTINTEN				 TD Lighting Solutions							
Checked By		Ibrahim OKMEN											
Approved By		Mesut CINAR											

TLS Teknoloji Sanayi ve Dis Ticaret A.S

This drawing is our property. It cant be reproduced or communicated without our written agreement.

CCT AND BINNING INFORMATION



LIFE TIME

MODEL NUMBER: NVW319B

Test Summary:

Data Set	Case Temperature [°C]	Ambient Temperature [°C]	Drive Current [mA]	Lumen Maintenance at 10K hours [%]	Chromaticity Shift (Δu'v') at 10K hours	TM-21 Projection L70(10K) [hours]	TM-21 Projection L80(10K) [hours]	TM-21 Projection L90(10K) [hours]
1	55	> 50	1050	98.5	0.0006	> 60000	> 60000	> 60000
2	55	> 50	1200	98.5	0.0007	> 60000	> 60000	> 60000
3	55	> 50	1500	98.2	0.0008	> 60000	> 60000	55500
4	85	> 80	1050	98.2	0.0008	> 60000	> 60000	> 60000
5	85	> 80	1200	98.0	0.0010	> 60000	> 60000	> 60000
6	85	> 80	1500	97.4	0.0014	> 60000	> 60000	45800
7	105	> 100	1050	97.6	0.0014	> 60000	> 60000	56600
8	105	> 100	1200	97.2	0.0016	> 60000	> 60000	44600
9	105	> 100	1500	88.2	0.0022	22800	15900	9870

LEGAL NOTICE

Product information provided by TLS Teknoloji Sistemleri San ve Dış Tic AŞ ("TLS") in this document is believed to be correct and accurate. TLS reserves the right to change/correct the specifications and other data or information relating to products without notice but TLS accepts no liability for errors that may appear in this document, howsoever occurring, or liability arising from the use or application of any information or data provided herein. Neither the supply of such information, nor the purchase or use of products conveys any licence or permission under patent, copyright, trademark or other intellectual property right of TLS or third parties.

Products sold by TLS are subject to its standard Terms and Conditions of Sale that are available on request. No warranty is given that products do not infringe the intellectual property rights of third parties, and furthermore, the use of products in certain ways or in combination with TLS, or non-TLS furnished equipments/components may infringe intellectual property rights of TLS.

The purpose of this document is to provide information only and it may not be used, applied or reproduced (in whole or in part) for any purpose nor be taken as a representation relating to the products in question. No warranty or guarantee express or implied is made concerning the capability, performance or suitability of any product, and information concerning possible applications or methods of use is provided for guidance only and not as a recommendation. The user is solely responsible for determining the performance and suitability of the product in any application and checking that any specification or data it seeks to rely on has not been superseded.

Products are intended for normal commercial applications. For applications requiring unusual environmental requirements, extended temperature range, or high reliability capability (e.g. military, or medical applications), special processing/testing/conditions of sale may be available on application to TLS.

CONTACT

TLS Teknoloji Sistemleri San ve Dış Tic AŞ

Akçaburgaz Mahallesi 3080. Sokak No:5 Esenyurt / İstanbul / TURKEY

info@tlsteknoloji.com
+90 444 27 33